



1

<p>Raised Push button - Spring</p> <p>Lateral connections</p>	<p>5/2</p> <p>Ordering code</p> <p>104.52.6.23/ C P</p> <p>BUTTON COLOR</p> <p>1 = Red 2 = Black 3 = Green 4 = Yellow</p> <p>CONNECTION TYPE</p> <p>L = Lateral P = Rear</p>	<p>Raised Push button - Spring</p> <p>Rear connections</p>				
<p>Weight gr. 105 Operating force 30N</p>		<p>Weight gr. 105 Operating force 30N</p>				
Operational characteristics	Fluid	Max working pressure	Operating Temperature	Flow rate at 6 bar with Δp=1	Orifice size	Working port size
	Filtered and lubricated air or not	10 bar	Min. -5°C Max. +50°C	90 NI/min	mm 2,5	ø4 tube

<p>Palm button 2 position</p> <p>Lateral connections</p>	<p>2/2</p> <p>Ordering code</p> <p>104. T 6.25. P F</p> <p>TYPE</p> <p>T 22 = 2 ways 32 = 3 ways</p> <p>CONNECTION TYPE</p> <p>P = Lateral R = Rear</p> <p>FUNCTION</p> <p>A = Norm. open N.O. C = Norm. closed N.C.</p>	<p>Palm button 2 position</p> <p>Rear connections</p>				
<p>Weight gr. 65 Operating force 19N Emergency - Rotate to unlock</p>		<p>Weight gr. 65 Operating force 19N Emergency - Rotate to unlock</p>				
Operational characteristics	Fluid	Max working pressure	Operating Temperature	Flow rate at 6 bar with Δp=1	Orifice size	Working port size
	Filtered and lubricated air or not	10 bar	Min. -5°C Max. +50°C	90 NI/min	mm 2,5	ø4 tube

<p>Palm button 2 position</p> <p>Lateral connections</p>	<p>5/2</p> <p>Ordering code</p> <p>104.52.6.25. P</p> <p>CONNECTION TYPE</p> <p>P = Lateral R = Rear</p>	<p>Palm button 2 position</p> <p>Rear connections</p>				
<p>Weight gr. 120 Operating force 32N Emergency - Rotate to unlock</p>		<p>Weight gr. 120 Operating force 32N Emergency - Rotate to unlock</p>				
Operational characteristics	Fluid	Max working pressure	Operating Temperature	Flow rate at 6 bar with Δp=1	Orifice size	Working port size
	Filtered and lubricated air or not	10 bar	Min. -5°C Max. +50°C	90 NI/min	mm 2,5	ø4 tube