

# GV5008

# Valves<sup>®</sup> O N L I N E



## PN16 Resilient Seated Gate Valve – WRAS Approved

- Fully WRAS Approved
- Complies with BS5163
- PN16 Rated
- Handwheel or Cap Top Option
- Epoxy Coating (Fusion Bonded)
- Flanged PN10/16

### > Description

The GV5008 is a ductile iron gate valve suitable for waterworks use. Complies with BS5163 and has a full WRAS Approval. PN16 flanges, handwheel or cap top operator and fusion bonded epoxy coating, ensure reliable performance. EPDM covered resilient seat and offered in sizes from 2" up to 12".

### > Options

Clockwise Close (Anti CW on request)  
Cap Top On request  
10" & 12" Not WRAS Approved

### Description

A ductile iron gate valve suitable for waterworks use. WRAS approved and complies to BS 5163. Flanged to PN10/16, handwheel operated as standard and offered in 2" up to 12".

### Beschreibung

Ein Absperrschieber aus duktilem Gusseisen, geeignet für den Einsatz in Wasserwerken. WRAS-zugelassen und entspricht BS 5163. Geflanscht nach PN10/16, handradbetätigt als Standard und in 2" bis 12" erhältlich.

### Descripción

Una válvula de compuerta de hierro dúctil adecuada para uso en obras hidráulicas. Aprobado por WRAS y cumple con BS 5163. Bridado a PN10/16, volante operado como estándar y ofrecido en 2" hasta 12".

### Description

Un robinet-vanne en fonte ductile adapté à une utilisation en aqueduc. Approuvé WRAS et conforme à la norme BS 5163. Bride à PN10/16, volant actionné en standard et proposé en 2" jusqu'à 12".

**WRAS**  
APPROVED  
PRODUCT



All information is sourced from our manufacturer's data and is intended for guidance only - Valves Online can accept no liability for changes, omissions or errors.

## > WRAS Gate Valve

- Complies with BS5163
- PN16 Rated
- Temperature -10°C to 70°C
- Hand wheel or Cap Top Operated
- Fusion Bonded Epoxy Coating
- Clockwise Close (Anti CW on Request)
- Fully WRAS approved
- Suitable for potable water

### Dimensions

Size	L	H	D	Kg
2"	178	240	175	10
2 1/2"	191	255	175	12.5
3"	203	280	255	17
4"	229	305	255	21
6"	267	417	305	38
8"	292	525	305	58
10"	<b>TBA</b>			
12"				

### Material

Body	Ductile Iron
Bonnet	Ductile Iron
Wedge	Ductile Iron with EPDM Coating
Thrust Collar	Brass
Stem Nut	Brass
Stem	Stainless Steel
O-Ring	EPDM
Gasket	EPDM
Gland	Ductile Iron
Wrench Nut	Ductile Iron
Handwheel	Ductile Iron

